

リミッタースペースなし / 全電力管内向け

主幹 (P.155~157参照) 40A、50A GBU-53・1J / 60A GBU-63・1J / 75A GBU-73・1KA / 100A GBU-103・1KA
分岐 (P.13参照) B-1EA / B-2EA

単3 主幹：単3中性線欠相保護付漏電遮断器

分岐回路数 + 予備回路数	主幹 (A)	分岐回路		仕様 区分	型式	露出形	埋込形	外形寸法 (mm)			盤定格 (A)
		2P1E	2P2E			メーカー希望 小売価格(円)	メーカー希望 小売価格(円)	タテ	ヨコ	フカサ	
8 ₊₀	40	6	2	●	AG3408ACL	32,800	39,100	314	364	95	60 
	50			●	AG3508ACL						
	60			●	AG3608ACL						
12 ₊₀	40	8	4	●	AG3412ACL	42,200	48,700	314	432	95	60 
	50			●	AG3512ACL						
	60			●	AG3612ACL						
16 ₊₀	40	12	4	●	AG3416ACL	51,600	58,300	314	500	95	60 
	50			●	AG3516ACL						
	60			●	AG3616ACL						
	75			●	AG3716ACL	57,600	64,300				100 
20 ₊₀	50	14	6	●	AG3520ACL	59,900	66,600	314	568	95	60 
	60			●	AG3620ACL						
	75			●	AG3720ACL	65,900	72,600			95	100 
	100			●	AG31020ACL	77,200	83,900				
24 ₊₀	60	18	6	●	AG3624ACL	69,300	76,300	314	661	95	60 
	75			●	AG3724ACL	75,300	82,300				100 
	100			●	AG31024ACL	86,300	93,300				
32 ₊₀	75	26	6	●	AG3732ACL	99,000	108,000	334	797	95	100 
	100			●	AG31032ACL	110,000	119,000				

(例) AG3408ACLの露出形の場合、AG3408ACLS3
AG3408ACLの埋込形の場合、AG3408ACLF3