

リミッタースペース付 / 北海道・東北・東京・中部・北陸・九州各電力管内向け

主幹 (P.155~157参照) **40A、50A GBU-53・1J / 75A GBU-73・1KA**  
 分岐 (P.13参照) **B-1EA / B-2EA**

**単3** 主幹：単3中性線欠相保護付漏電遮断器 入線最大容量 38mm<sup>2</sup>

分岐回路数 + 予備回路数	主幹 (A)	分岐回路		仕様 区分	型式	温水器用 ブレーカ (A)	露出形		外形寸法(mm)			盤定格 (A)
		2P1E	2P2E				メーカー希望 小売価格(円)	タテ	ヨコ	フカサ		
<b>8</b> <sub>+0</sub>	40	6	2	●	ALG3408PATB3	30		45,600	314	568	110	60 
	40			●	ALG3408PATB4	40	48,600					
<b>10</b> <sub>+0</sub>	40	8	2	●	ALG3410PATB3	30		48,600	314	627	110	60 
	40			●	ALG3410PATB4	40	51,600					
<b>12</b> <sub>+0</sub>	50	8	4	●	ALG3512PATB3	30		52,600	314	661	110	60 
	50			●	ALG3512PATB4	40	55,600					
<b>16</b> <sub>+0</sub>	50	12	4	●	ALG3516PATB3	30		60,600	334	729	110	60 
	50			●	ALG3516PATB4	40	63,600					
	75			●	ALG3716PATB3	30	67,200	75 				
	75			●	ALG3716PATB4	40	70,200					
<b>20</b> <sub>+0</sub>	50	14	6	●	ALG3520PATB4	40		71,600	334	797	110	60 
	75			●	ALG3720PATB4	40	78,200	75 				

温水器用ブレーカ30Aには安全ブレーカ(B-2EA 30A)、40Aには配線用遮断器(B-53EA 40A)を使用しています。

リミッタースペースなし / 全電力管内向け

主幹 (P.155~157参照) **40A、50A GBU-53・1J / 75A GBU-73・1KA**  
 分岐 (P.13参照) **B-1EA / B-2EA**

**単3** 主幹：単3中性線欠相保護付漏電遮断器 入線最大容量 38mm<sup>2</sup>

分岐回路数 + 予備回路数	主幹 (A)	分岐回路		仕様 区分	型式	温水器用 ブレーカ (A)	露出形		外形寸法(mm)			盤定格 (A)
		2P1E	2P2E				メーカー希望 小売価格(円)	タテ	ヨコ	フカサ		
<b>8</b> <sub>+0</sub>	40	6	2	●	AG3408PATB3	30		38,500	314	500	95	60 
	40			●	AG3408PATB4	40	41,500					
<b>10</b> <sub>+0</sub>	50	8	2	●	AG3510PATB3	30		41,800	314	534	95	60 
	50			●	AG3510PATB4	40	44,800					
<b>12</b> <sub>+0</sub>	50	8	4	●	AG3512PATB3	30		45,100	314	568	95	60 
	50			●	AG3512PATB4	40	48,100					
<b>14</b> <sub>+0</sub>	50	10	4	●	AG3514PATB3	30		48,400	314	627	95	60 
	50			●	AG3514PATB4	40	51,400					
<b>16</b> <sub>+0</sub>	50	12	4	●	AG3516PATB3	30		51,600	314	661	95	60 
	50			●	AG3516PATB4	40	54,600					
	75			●	AG3716PATB3	30	58,200	75 				
	75			●	AG3716PATB4	40	61,200					
<b>20</b> <sub>+0</sub>	50	14	6	●	AG3520PATB4	40		62,600	334	729	95	60 
	75			●	AG3720PATB4	40	69,200	75 				
<b>24</b> <sub>+0</sub>	75	18	6	●	AG3724PATB4	40		77,200	334	797	95	75 

温水器用ブレーカ30Aには安全ブレーカ(B-2EA 30A)、40Aには配線用遮断器(B-53EA 40A)を使用しています。