

●電動機の過負荷・拘束・欠相保護用

欠相サーマルリレー



外形寸法P.710~



型式	適合電動機容量 (kW)		ヒータ仕様		納期区分	ご注文品番	標準価格 (円)	質量 (kg)
	3φ200V	3φ400V	中心値(A)	調整範囲(A)				
TR12B-2E 電磁接触器組合せ専用 (MP-10H) (MR-10BH) (MP-11H)			0.2	0.16~0.24	●	UQB002	4,550	0.1
			0.3	0.24~0.36	●	UQB003		
			0.4	0.32~0.48	●	UQB004		
			0.5	0.4~0.6	●	UQB005		
			0.6	0.5~0.7	●	UQB006		
			0.8	0.7~0.9	●	UQB008		
	0.2	0.4	1.2	1.0~1.4	●	UQB02		
	0.3	-	1.4	1.1~1.7	●	UQB04		
	-	0.75	1.8	1.4~2.2	●	UQB06		
	0.4	0.75	2.4	2.0~2.8	●	UQB08		
	-	-	3.0	2.4~3.6	●	UQB10		
	0.75	1.5	3.8	3.0~4.5	●	UQB12		
	-	2.2	5.0	4~6	●	UQB14		
	1.5	3.7	6.8	5.5~8.0	●	UQB16		
2.2	-	9.0	7~11	●	UQB18			
-	5.5	11	9~13	●	UQB20			
TR20B-2E	0.2	0.4	1.2	1.0~1.4	●	UQE02	4,980	0.15
	0.3	-	1.4	1.1~1.7	●	UQE04		
	-	0.75	1.8	1.4~2.2	●	UQE06		
	0.4	0.75	2.4	2.0~2.8	●	UQE08		
	-	-	3.0	2.4~3.6	●	UQE10		
	0.75	1.5	3.8	3.0~4.5	●	UQE12		
	-	2.2	5.0	4~6	●	UQE14		
	1.5	3.7	6.8	5.5~8.0	●	UQE16		
	2.2	-	9.0	7~11	●	UQE18		
	-	5.5	11	9~13	●	UQE20		
3.7	7.5	15	12~18	●	UQE22			
TR25B-2E 電磁接触器組合せ専用 (MP-25H)	5.5	11	20	16~24	●	UQH02	5,400	0.17
TR50B-2E	2.2	-	9	7~11	●	UQK02	8,760	0.25
	-	5.5	11	9~13	●	UQK04		
	3.7	7.5	15	12~18	●	UQK06		
	5.5	11	20	16~24	●	UQK08		
	7.5	15	28	22~34	●	UQK10		
	11	18.5	40	32~48	●	UQK12		
TR80B-2E	5.5	11	20	16~24	●	UQN02	10,400	0.36
	7.5	15	28	22~34	●	UQN04		
	11	18.5	40	32~48	●	UQN06		
	15	30	55	45~65	●	UQN08		
	18.5	37	67	55~80	●	UQN10		
TR150B-2E 電磁接触器組合せ専用 (MP-100HA) (MP-125HA) (MP-150HA)	22	45	80	65~95	●	UQQ02	12,200	0.37
	30	55	105	90~120	●	UQQ04		
	37	75	130	110~150	●	UQQ06		

復帰方式は手動・自動兼用です。(手動復帰で出荷)

単独取付け: 12B、25B、150Bは別途お問合せください。

標準サーマルリレー、欠相サーマルリレーともヒータ中心値が130Aを超える場合、サーマルリレーとCTの組合せとなります。

電磁接触器・開閉器