

極数(P)・素子数(E)・フレーム(AF)		2P・1E・30AF																							
型式		GB-1ZA																							
定格使用電圧Ue(AC)		100V																							
定格インパルス耐電圧 Uimp(kV)		—																							
定格感度電流		15mA						30mA																	
最大動作時間		0.1秒																							
慣性不動作時間		—																							
定格電流 ご注文品番	5A	1ZA0515								5A	1ZA0530														
				6A	1ZA0615							6A	1ZA0630												
				10A	1ZA1015							10A	1ZA1030												
							15A	1ZA1515								15A	1ZA1530								
							20A	1ZA2015								20A	1ZA2030								
							30A	1ZA3015								30A	1ZA3030								
標準価格(円)		5,400				4,300				4,000				5,400				4,300				4,000			
外観及び外形寸法(mm)		安全ブレーカ互換性寸法																							
B A D C A 70 B 32 C 40 D 57																									
定格遮断容量 (kA)	100V	1.5																							
	JIS C 8222 Ann2(Icn)																								
	AC																								
	200V																								
表面形 端子仕様		ソルダレス端子方式(当座金付)																							
接続可能最大電線(mm ²)		8																							
取付可能付属装置	裏面形	SD	—																						
	接続方式	埋込形	FP	—																					
	補助スイッチ	AX	—																						
	警報スイッチ	AL	—																						
	テストリード線引出し	TBL	—																						
	端子台	TB	—																						
	キャップ式	LC	別売(LC-03)																						
	ハンドルロック	施錠式	HL	—																					
	外部操作ハンドル	HA	—																						
	バリア	BA	—																						
端子カバー	表面形	TMC	付 属																						
	裏面形	BTC	—																						
逆接続		可 能																							
適合JIS規格		JIS C 8222 Ann2																							
過電流引外し方式		熱動																							
製品質量(kg)		0.13																							
一梱入数		50																							
漏電表示		無																							
特性、寸法図記載ページ		B-210																							

■ 100/200Vは単相3線式を表します。 ■ 付属装置価格は「付属装置」の項を参照。P.B-245 ~
■ 短ハンドルは受注品です。

ハンドルキャップ

- 遮断器のハンドルをON、OFFいずれかの状態で操作禁止を表示する部品です。
- ハンドルキャップは10個単位でご注文ください。



■ 価格/1個

型式	LC-03
ご注文品番	ULC03
納期区分	
標準価格(円)	120