


2P・2E・30AF												極数(P)・素子数(E)・フレーム(AF)						
GB-2ZA												型式						
100-100/200-200V												定格使用電圧Ue(AC)						
—												定格インパルス耐電圧 Uimp(kV)						
15mA						30mA						定格感度電流						
0.1秒												最大動作時間						
—												慣性不動作時間						
5A	2ZA0515					5A	2ZA0530					定格電流 ご注文品番						
		6A	2ZA0615					6A	2ZA0630									
		10A	2ZA1015					10A	2ZA1030									
				15A	2ZA1515					15A	2ZA1530							
				20A	2ZA2015					20A	2ZA2030							
				30A	2ZA3015					30A	2ZA3030							
6,000			4,800			4,600			6,000			4,800			4,600			標準価格(円)
安全ブレーカ互換性寸法												外観及び外形寸法(mm)						
																		
A 70 B 32 C 40 D 57																		
1.5												100V		JIS C 8222 Ann2(Icn) 定格遮断容量 (kA)				
1.5												100/200V						
1.0												200V						
												415V						
ソルダレス端子方式(当座金付)												表面形 端子仕様						
8												接続可能最大電線(mm ²)						
—												SD 裏面形 接続方式		取 付 可 能 付 属 装 置				
—												FP 埋込形						
—												AX 補助スイッチ						
—												AL 警報スイッチ						
—												TBL テストリード線引出し						
—												TB 端子台						
別売(LC-03)												LC キャップ式 ハンドルロック						
—												HL 施錠式						
—												HA 外部操作ハンドル						
—												BA バリア						
付 属												TMC 表面形 端子カバー						
—												BTC 裏面形						
可 能												逆接続						
JIS C 8222 Ann2(● JISC8201-2-2 Ann2)												適合JIS規格						
熱動												過電流引外し方式						
0.13												製品質量(kg)						
50												一梱入数						
無												漏電表示						
B-210												特性、寸法図記載ページ						

■100/200Vは単相3線式を表します。■付属装置価格は「付属装置」の項を参照。P.B-245～
■短ハンドルは受注品です。