


3P・3E・100AF													極数(P)・素子数(E)・フレーム(AF)															
GB-103EC						GBL-103EC (時延形)							型式															
100-200V			200-415V			100-200V			200-415V				定格使用電圧U _e (AC)															
6kV													定格インパルス耐電圧 U _{imp}															
15mA		30mA		100/200/500mA		15mA		30mA		100/200/500mA		100/200/500mA			定格感度電流													
0.1秒						0.45秒							最大動作時間															
—						0.15秒							慣性不動作時間															
50A (11kW)	—	—	◎	103EC0530	—	—	—	—	◎	103EC05304	⑤	103EC05W24	—	—	●	103EC05W2L4	定格電流 ご注文品番 表面形 () AC200V時の 適用モータ容量 (kW) です。											
60A (15kW)	⑦	103EC0615	◎	103EC0630	◎	103EC06W2	⑦	103EC06154	◎	103EC06304	⑤	103EC06W24	◎	103EC06W2L	⑦	103EC06W2L4												
75A (18.5kW)	⑦	103EC0715	◎	103EC0730	◎	103EC07W2	⑦	103EC07154	◎	103EC07304	⑤	103EC07W24	◎	103EC07W2L	⑦	103EC07W2L4												
100A (22kW)	◎	103EC1015	◎	103EC1030	◎	103EC10W2	⑦	103EC10154	◎	103EC10304	⑤	103EC10W24	◎	103EC10W2L	◎	103EC10W2L4												
表面形		裏面形 (注)		埋込形 (注)		表面形		裏面形 (注)		埋込形 (注)		表面形		裏面形 (注)		埋込形 (注)		接続方式										
21,200		25,700		30,600		22,500		27,000		31,900		25,700		30,200		35,100		27,000		31,500		36,400		標準価格 (円)				
モータ保護兼用																		外観及び外形寸法 (mm)  () 内は端子 カバー付寸法										
A 130 (160) B 75 C 60 D 80																												
10/3						10/3						100V											JIS C 8201-2-2 Ann2(lcu/lcs)		定格遮断容量 kA			
10/3			10/3			10/3			10/3			100/200V 200V																
			5/3						5/3			415V																
圧着端子方式 (圧着端子付属)													表面形 端子仕様															
60													接続可能最大電線 (mm ²)															
●	●	●	●			●			●					SD 裏面形		接続方式		取付可能 付属装置										
●	●	●	●			●			●					FP 埋込形														
⑦	⑦	⑦	●			●			⑦					AX 補助スイッチ														
⑦	⑤ (100A◎)	⑦ (100A◎)	●			●			⑦					AL 警報スイッチ														
⑦	⑦	⑦	●			●			⑦					TBL テストリード線引出し														
可能 (縦形)													TB 端子台															
有													TRB トリップボタン															
別売 (LC-153EB)													LC キャップ式					ハンドルロック										
●													HL 施錠式															
—													HA 外部操作ハンドル															
別売 (PHS-2T)													BA バリア															
付 属													TMC 表面形					端子カバー										
裏面形付属													BTC 裏面形															
可 能													逆接続															
JIS C 8201-2-2 Ann2													適合JIS規格															
熱動電磁													過電流引外し方式															
0.75													製品質量(kg)															
10													一梱入数															
有													漏電表示															
B-214													特性、寸法図記載ページ															

中感度形(定格感度電流100mA) (最大動作時間0.1秒)		
50A	100mA	③ 103EC05100



中感度形(定格感度電流100mA,200mA) (時延形 最大動作時間0.45秒)			
定格電流	感度電流	100-200V	200-415V
50A	100mA	● 103EC05100L	● 103EC05100L4
	200mA	● 103EC05200L	● 103EC05200L4
60A	100mA	● 103EC06100L	● 103EC06100L4
	200mA	● 103EC06200L	● 103EC06200L4
75A	100mA	● 103EC07100L	● 103EC07100L4
	200mA	● 103EC07200L	● 103EC07200L4
100A	100mA	● 103EC10100L	● 103EC10100L4
	200mA	● 103EC10200L	● 103EC10200L4

■付属装置価格は「付属装置」の項を参照。P.B-245～ ■適合圧着端子 P.B-269
(注) ご注文品番の後に裏面形はS、埋込形はFをつけてご注文ください。
(フラッシュプレート:マンセル5Y7/1)

●時延形の価格はP.B-268を参照してください。